

Cooper couplings

Sleeves made from electrolytic copper with a coating of tin to improve electrical contact. Incorporate an inspection hole.



CERTIFICATIONS



CHARACTERISTICS

- Made in electrolytic copper in 99% with tin coated.
- Designed to offer high mechanical tensile strength, vibration and electrical conductivity.
- Suitable for the connection of copper conductors (section 1.5-400 mm²) in power cable with electronic equipment.
- With inspection hold.
- With recess at the ends to facilitate cable entry.
- Working temperature: -15 C to 150 C.

TECHNICAL SPECIFICATIONS/ DIMENSIONS

| Artículo | Code | Packing | D (mm) | d (mm) | L (mm) |
|----------|---------|---------|--------|--------|--------|
| KCC 1,5 | 0779978 | 100 | 3,5 | 2,5 | 20 |
| KCC 2,5 | 0779979 | 100 | 4 | 3 | 20 |
| KCC 4 | 0779980 | 100 | 4,8 | 3,5 | 20 |
| KCC 6 | 0779981 | 100 | 5,5 | 4,1 | 25 |
| KCC 10 | 0779982 | 100 | 6,7 | 5 | 30 |
| KCC 16 | 0779983 | 100 | 7,5 | 5,8 | 35 |
| KCC 25 | 0779984 | 100 | 9 | 7,2 | 40 |
| KCC 35 | 0779985 | 100 | 10,5 | 8,5 | 45 |
| KCC 50 | 0779986 | 100 | 12,5 | 10,1 | 50 |
| KCC 70 | 0779987 | 100 | 14,5 | 11,7 | 55 |
| KCC 95 | 0779988 | 50 | 17 | 13,8 | 60 |
| KCC 120 | 0779989 | 25 | 19,5 | 15,9 | 65 |
| KCC 150 | 0779990 | 25 | 20,5 | 16,7 | 70 |
| KCC 185 | 0779991 | 25 | 23,5 | 19,1 | 75 |
| KCC 240 | 0779992 | 12 | 26 | 21,4 | 80 |
| KCC 300 | 0779993 | 6 | 30 | 24,6 | 85 |
| KTCC 400 | 0779994 | 6 | 34 | 27,4 | 90 |

