

KOBAN



FEATURES

- ✓ Simple and integrative structure design, easy in installation.
- ✓ Housing with high heating conductive aluminum material, excellent heating radiation performance.
- ✓ High luminous efficacy, small lumen depreciation, long lifespan



TECHNICAL SPECIFICATIONS

	KLED-SSX-30W 8768156	KLED-SSX-60W 8768155	KLED-SSX-90W 8768154	KLED-SSX-120W 8768153
LED light source	SMD2835	SMD2835	SMD2835	SMD2835
Solar panel	6V/6W	6V/9W	6V/12W	6V/15W
Battery capacity	6AH 3.2V	9AH 3.2V	12AH 3.2V	15AH 3.2V
Lumen	300±10%	500±10%	800±10%	1100±10%
Power	30W	60W	90W	120W
Function	Radar + light control	Radar + light control	Radar + light control	Radar + light control
Color temp.	6500K	6500K	6500K	6500K
Lifetime	50000hr	50000hr	50000hr	50000hr
Total harmonic distortion	<10%	<10%	<10%	<10%
Work humidity	20-80%RH	20-80%RH	20-80%RH	20-80%RH
IP Rating	IP65	IP65	IP65	IP65

	KLED-SSX-30W 8768156	KLED-SSX-60W 8768155	KLED-SSX-90W 8768154	KLED-SSX-120W 8768153
Lighting area	60m ²	80m ²	110m ²	150m ²
Material	ABS	ABS	ABS	ABS
Beam angle	120°	120°	120°	120°
Size(mm)	395*210*60mm	495*240*70mm	635*260*70mm	785*280*70mm

DIMENSIONS

