

KOBAN



FEATURES

- ✓ Simple and integrative structure design, easy in installation.
- ✓ Housing with high heating conductive aluminum material, excellent heating radiation performance.
- ✓ High luminous efficacy, small lumen depreciation, long lifespan



TECHNICAL SPECIFICATIONS

	KLED-SLX-20W	KLED-SLX-40W	KLED-SLX-60W
LED light source	SMD3030	SMD3030	SMD3030
Solar panel	6V 6W	6V 9W	6V 12W
Lumen	420lm	520lm	650lm
Lithium battery	3.2V/ 5AH	3.2V/ 9AH	3.2V/ 12AH
Discharging time	8-12hours	8-12hours	8-12hours
Power	20W	40W	60W
CRI	Ra>70	Ra>70	Ra>70
Color temp.	6500K	6500K	6500K
Lifetime	50000hr	50000hr	50000hr
Total harmonic distortion	<10%	<10%	<10%
Work humidity	20-80%RH	20-80%RH	20-80%RH
IP Rating	IP66	IP66	IP66

	KLED-SLX-20W	KLED-SLX-40W	KLED-SLX-60W
Power factor	>0.9	>0.9	>0.9
Beam angle	120°	120°	120°
Material	Aluminum	Aluminum	Aluminum
Installation height	3-5m	3-5m	3-5m
Size(mm)	L395*W210*H60mm	L495*W240*H70mm	L635*W260*H70mm

DIMENSIONS

KLED-SLX-XXW

